

# Product datasheet

Specifications



## APC Easy UPS On-Line, 5kVA/5kW, Rackmount 5U, 230V, Hard wire 3-wire(1P+N+E) outlet, Intelligent Card Slot, LCD, Extended Runtime, W/ Rail Kit

SRV5KRIL-IN

### Overview

<b>Presentation</b>	High quality, Double-conversion On-line UPS designed for essential power protection needs even in the most unstable power conditions.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	230 V AC
<b>Other Input Voltage</b>	220 V 240 V
<b>Main Output Voltage</b>	230 V
<b>Other Output Voltage</b>	220 V 240 V
<b>Rated power in W</b>	5000 W
<b>Rated power in VA</b>	5000 VA
<b>Output connector type</b>	Hard wire 3-wire (1P + N + E) 1
<b>Number of rack unit</b>	5U

### Batteries & Runtime

<b>Battery type</b>	Lead-acid battery
<b>Battery voltage</b>	240 V
<b>Number of battery filled slots</b>	1
<b>Number of battery free slots</b>	0
<b>Battery recharge time</b>	5 h
<b>Battery charger power</b>	469 W rated
<b>Battery option</b>	SRV240RBP-9A 1 3240 VAh SRV240RBP-9A 2 4225 VAh SRV240RBP-9A 3 5616 VAh SRV240RBP-9A 4 7056 VAh

### General

<b>Max runtime</b>	8 min
<b>Number of power module filled slots</b>	0

---

Number of power module free slots	0
-----------------------------------	---

---

Redundant	No
-----------	----

---

## Physical

---

Colour	Black (RAL 7010)
--------	------------------

---

Height	21.95 cm
--------	----------

---

Width	43.8 cm
-------	---------

---

Depth	61.5 cm
-------	---------

---

Net weight	78 kg
------------	-------

---

Mounting location	Front
-------------------	-------

---

Mounting preference	Lower
---------------------	-------

---

Mounting mode	Rack-mounted with kit
---------------	-----------------------

---

USB compatible	No
----------------	----

---

Mounting position	Horizontal
-------------------	------------

---

## Input

---

Switching current capacity	50 A
----------------------------	------

---

Input voltage limits	110...300 V half load 176...300 V full load
----------------------	--

---

Number of input connectors	1 hard wire 3-wire (1P + N + E)
----------------------------	---------------------------------

---

Network frequency	40...70 Hz auto sensing
-------------------	-------------------------

---

## Output

---

Maximum configurable power in VA	5000 VA
----------------------------------	---------

---

Maximum configurable power in W	5000 W
---------------------------------	--------

---

Output frequency	50/60 Hz +/- 3 Hz sync to mains
------------------	---------------------------------

---

UPS type	Double conversion online
----------	--------------------------

---

Wave type	Sine wave
-----------	-----------

---

Efficiency	94 % (full load)
------------	------------------

---

Additional information	Configurable for 220 : 230 or 240 nominal output voltage
------------------------	--

---

Bypass type	Internal bypass (automatic and manual)
-------------	--

---

Crest factor	3 : 1
--------------	-------

---

## Conformance

---

Product certifications	BIS
------------------------	-----

---

## Environmental

---

Ambient air temperature for operation	0...40 °C
---------------------------------------	-----------

---

Relative humidity	0...95 % non-condensing
-------------------	-------------------------

---

Operating altitude	0...3000 m
--------------------	------------

---

Ambient air temperature for storage	-20...60 °C
-------------------------------------	-------------

---

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

---

Storage altitude	0...15000 m
Acoustic level	55 dBA
IP degree of protection	IP20

## Communications & Management

Alarm	Audible and visible alarms : prioritized by severity
Emergency power off	Yes
Control panel	Multifunction LCD status and control console

## Surge Protection and Filtering

Surge energy rate	600 J
-------------------	-------

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	49 cm
Package 1 Width	87 cm
Package 1 Length	60 cm
Package 1 Weight	88 kg

## Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------

## Recommended replacement(s)