

Description

OmniLeak offers a wide range of accessories and connectors specific to the user requirements of the leak detection system (Water, Acid & Hydrocarbon).

OL-SLDM



Addressable Digital Module for Water & Acid Sensing Cable

OL-SLDM module is a smart electronic module equipped with heavy-duty connectors, able to withstand exposure to water & acid. It is made with durable material so that it can remain reliable and responsive throughout its service life. The connectors are IP68 and suitable for outdoor applications

OL-HCM



Addressable Digital Module for Hydrocarbon Sensing Cable

The OL-HCM module is a heavy-duty connector, able to withstand exposure to hydrocarbons. It is made with durable material so that it can remain reliable and responsive throughout its service life.

OL-LEADER



Leader Cable 5m with Female Connector

The OL-LEADER is a 5m neutral cable with a female connector which allows the circuit to be started from the detection unit.

The Company endeavors to continuously improve and renew its products, for this reason the technical data and contents of this document may undergo variations without prior notice. For correct installation and use, the Company can guarantee only the data indicated in the instruction manual supplied with the products. Product and Company names and logos referenced may be either trademarks or registered trademarks of their respective companies. We reserve the right to make modifications and improvements.

OL-END



Digital End Termination

End of circuit socket for sensing cables. Each sensing cable zone must be terminated with an OL-END termination plug.


OL-JUMPER



Jumper Neutral Cable 5m with Male and Female Connectors

The OL-JUMPER is a 5m neutral cable with a male connector and a female connector which allows you to connect two liquid leak detection cables.

OL-CLIPS



Hold-Down Clips for Sensing Cables with Adhesive

OL-CLIPS are used to hold and position the cables in the exact location where user requires. It is recommended the clips to be installed at intervals of 1m and/or every change of direction if less than 1m.

OL-TAGS



Identity Tags for Sensing Cables

OL-TAGS recommended to be attached on each sensing cable at intervals of no greater than 3m. Each tag will have zone location, sensor cable number and the metre location.

OL-BUS



Neutral Cable -

OL-BUS is a communication cable which allows connection between alarm terminal and sensing cables and also provides connection between two sensing cables. The neutral cable can also be used to create an extension between two zones.

Manufacturer

OmniLeak by Dagman S.A.S - France
32-34 Rue des Osiers 78 310 COIGNIERS
Paris, France.

Email: admin@omnileak-me.com

Web: www.omnileak-me.com



Certifications



Valid only when used with the appropriate certified acquisition devices

© 2022 All Rights Reserved OmniLeak
OL_ACCESORIES_Rev02_2021