

Product datasheet

Specifications



Maintenance Bypass Panel, single unit, 10-400kVA 400V wallmount, for Easy UPS 3-Phase

E3MBP60K400H

Overview

Presentation	Maintenance bypass panel for complete isolation of the UPS during service operations.
Lead Time	Usually Ships within 2 Weeks

Main

Product Or Component Type	Panel
Provided Equipment	Installation manual

Physical

Colour	White
Height	105 cm
Width	75 cm
Depth	35 cm
Net Weight	75 kg

Conformance

Product Certifications	IEC 62040-1-1
------------------------	---------------

Environmental

Ambient Air Temperature For Operation	0...40 °C
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature For Storage	-25...55 °C
Storage Relative Humidity	0...95 % non-condensing

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	62 cm
Package 1 Width	85 cm
Package 1 Length	116 cm
Package 1 Weight	98.792 kg

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

✓ Reach Free Of Svhc

✓ Toxic Heavy Metal Free

✓ Mercury Free

✓ Rohs Exemption Information [Yes](#)

Reach Regulation [REACH Declaration](#)

Eu Rohs Directive [Compliant](#)
[EU RoHS Declaration](#)

China Rohs Regulation [China RoHS declaration](#)
