

Product datasheet

Specifications



InRow DX 300mm 30kW

ACRD301S

Main

Compressor type	Scroll
Air flow	1604.6 l/s
provided equipment	Installation guide Integrated network management Network management card Optional concrete pad User manual

Physical

Height	199.1 cm
Width	30 cm
Depth	109.5 cm
net weight	159.98 kg

Input

Input power	850 W
-------------	-------

Environmental

Ambient air temperature for operation	-25...46 °C
Ambient air temperature for storage	-20...46 °C
Operating altitude	0...10000 ft
Acoustic level	77.1 dBA

Communications & Management

control panel	Multifunction LCD status and control console
---------------	--

Accuracy

Air discharge option	Horizontal
----------------------	------------

Contractual warranty

Warranty	1 year on-site repair or replace with factory authorized Start-Up
----------	---

Excluding VAT, FCA Jabal Ali & are subject to change – check with your local distributor.

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive

Not applicable, out of EU RoHS legal scope
